



## TCS Choice WALL MOUNT 1 LGX PATCH PANEL









Heat Resistant Splice Chip - Installing in a hot climate? Our enhanced splice chip is designed for extreme climates and screws down for a secure connection. PN: ST-PASD-24



Grommeted Non-captive Entry Portals -Protects cables from sharp edges and makes future moves, adds and changes easier



DIN Rail Kit - Includes two sturdy brackets to mount to standard 35mm DIN Rail PN: FPP-01-W-DINRAIL



Universal Compression Grommet -Replaces zip cords for strain relief providing a secure connection PN: CF-B

## **MORE FEATURES**

- Space saving panel with ample room for cable routing
- Non-captive front and rear entry with protective edges
- Rear SC cut-outs Allows for a wallmount MTP® cassette or splitter

## **SPECIFICATIONS**

- Dimensions: 5.56" W x 6.125" H x 1.125" D
- Panels: (1) Total Cable Solutions or LGX Adapter Panels (see individual panel capacities)
- Fiber Capacity: (12) Splice, (24) Patch
- Material: 18 Gauge Steel
- Coating: black electrostatic polyester powder coat paint

## WHAT'S INCLUDED

- 4 Cable ties
- 1 Splice chip
- 2 Rubber cable entry grommets
- 4 Cable management clips
- 1 Warning label
- 1 Port identification label



