







Lock down your data center power cords with the P-Lock from Total Cable Solutions. As more manufacturers are offering locking outlets, the P-Lock is quickly becoming the standard to prevent accidental disconnection of power cords from PDU outlets. P-Locks are designed with "P-shaped" clips on each side of the plug housing. These clips produce an audible "click" when inserted assuring a secure locking fit between the plug and the outlet.

P-Locks are available in Black, Blue and Red to easily identify main and redundant power sources at a glance. Color coding with P-Locks adds peace-of-mind and ensures maximum uptime.

FEATURES

- Male connector locks securely into locking PDU*
- UL Listed
- Ships coiled, never kinked
- Lifetime Warranty

P-Lock C14 to C13

- Electrical Rating: 10 Amp, 250 Volt
- Temperature Rating: to 105° C
- Approvals: UL Listed, RoHS Compliant
- Jacket: SVT, 18 AWG

SPECIFICATIONS

P-Lock C20 to C19

- Electrical Rating: 20 Amp, 250 Volt
- Temperature Rating: to 105° C
- Approvals: UL Listed, RoHS Compliant
- Jacket: SJT Jacket, 12 AWG

P-Lock C14 to C15

- Electrical Rating: 15 Amp, 250 Volt
- Temperature Rating: to 105° C
- Approvals: UL Listed, RoHS Compliant
- Jacket: SJT Jacket, 14 AWG













Easy pinch design allows quick release from outlets



P-tabs ensure that P-Lock cables lock securely into Raritan® SecureLock™ * and ServerTech lockable PDUs









all Raritan® iPDUs manufactured after June 2012 with part number prefix "PX2"

The SureFIT™ Locking Sleeve creates a strong connection and prevents power cables from being accidentally dislodged. Use SureFIT™ on the female end of your P-Lock Locking Power cable. Available for C13 and C19.



 While P-Lock Locking Cables will work in ANY PDU, they are 100% compatible with Raritan® SecureLock™ locking PDUs as well as ServerTech® Lockable PDUs. Tests have shown that P-Locks will lock into other major brands' locking PDUs as well.

*Total Cable Solutions is not aphiliated with Raritan® and SecureLock™ products or Server Technologies® and ServerTech™ products.



1 FEMALE SIDE MALE SIDE **JACKET TYPE**

C13 = 3C15 = 5

C19 = 9

C14 = FC20 = T SJT = JSVT = V 4 LABELS Shipped w/ Label = L

AMPERAGE

10 AMP = 115 AMP = 520 AMP = 0 6 VOLTAGE 250v = 2

7 COLOR

Black = BKBlue = BLGreen = GN

Red = RD

8 LENGTH 3-Digit Length

Examples: 001, 0.50, 01.5 **UNIT OF MEASURE** Feet = F